



F76/253 - IMC Ventus V90  
Bottle Cooler [Front  
Load] - Glass Door -  
Stainless Steel Frame - H  
900 mm - W 900 mm - D  
450 mm - R290

Ventus forms part of our dynamic range of bottle coolers. With over 150 options you can be assured that the feature packed V90 can be tailored to suit any bar environment.

- ✓ Reduced 450mm depth
- ✓ Wide range of options available to customise your bottle cooler, ensure a perfect fit in any bar.
- ✓ Elegant, flexible storage for up to 156 bottles
- ✓ Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times.
- ✓ Electronic temperature control keeps drinks at the perfect serving temperature
- ✓ Energy efficient EcoSmart controller - at the touch of a button, put the bottle cooler into its most economical state until next required
- ✓ Sleek stainless steel interior and LED lighting to enhance display
- ✓ Twin double-glazed lockable doors for enhanced security
- ✓ UK 3 pin plug allows users to simply plug in and switch on

**Specifications**

**Summary**

<b>Brand</b>	IMC
<b>Range</b>	Ventus
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105197645

**Power and Performance**

<b>Total Power kW</b>	0.410
<b>Temperature Range °C</b>	2-6
<b>IP Rating</b>	IPX1
<b>Temperature Control</b>	Electronic

**Key Specifications**

<b>Door Hinge</b>	Left; Right
<b>Door Location</b>	Front
<b>Lockable Door</b>	Yes
<b>Colour</b>	Stainless Steel
<b>Number of Doors</b>	2
<b>Door Type</b>	Standard frame, glass
<b>Number of Shelves included</b>	2
<b>Number of Shelf Positions</b>	29
<b>Refrigerant Type</b>	R290
<b>Type of Lighting</b>	LED

**Capacity**

<b>Capacity Bottles</b>	156
<b>Capacity Litres</b>	204

Weights and Dimensions		Supply Connections	
------------------------	--	--------------------	--

Unit Height (External) mm	900	Requires Installation	No
Unit Width (External) mm	900	Requires Electrical Supply	Yes
Unit Depth (External) mm	450	UK 3 Pin Plug	Yes
Height (Internal) mm	755	Requires Hardwiring	No
Width (Internal) mm	826	Electrical Supply Rating Watts	410
Depth (Internal) mm	327	Single Phase Amps	1.71
Shelf Dimensions Width mm	810	Single Phase Voltage	240
Shelf Dimensions Depth mm	323		
Net Weight Kg	0		

Shipping	
----------	--

Packed Weight Kg	0
Packed Height cm	0
Packed Width cm	0
Packed Depth cm	0

Available Options	
-------------------	--

<b>Door Type</b>	
VS416	VS416 - Change to Fixing Point Solid Door
VS428	VS428 - Change to Solid Door
VS469	VS469 - Change to Frameless Glass Door
VS472	VS472 - Change to Fixing Point Glass Door
<b>Wood Cladding</b>	
VS405	VS405 - Wood Cladding Kit - Add to F-Point Door
<b>Handle Type</b>	
VS446HOR	VS446HOR - Short Horizontal Handle
VS446VER	VS446VER - Short Vertical Handle
VS447HOR	VS447HOR - Long Horizontal Handle
VS447VER	VS447VER - Long Vertical Handle
<b>Lighting</b>	
VS855	VS855 - Change to Red LED Lights
VS856	VS856 - Change to Green LED Lights
VS857	VS857 - Change to Blue LED Lights
<b>Shelving Type</b>	
VS403	VS403 - Change to Perforated Shelving
<b>EU Plug</b>	
VS401	VS401 - Change to EU Plug
<b>De-Gassed</b>	
VS1017	VS1017 - De-Gassed for Air Freight

Available Accessories	
-----------------------	--

A12/097	NULL
S76/124	Perforated Shelf - for V90 - 450D



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm